Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-82. (Canceled)

83. (Currently Amended) A print control system <u>configured</u> ~~adapted~~ to control a <u>single</u> digital printer having a first machine-readable ink and a second ink ~~, or inks,~~ that <u>is</u> ~~is/are~~ not machine-readable at the same wavelength as said first ink, said system being configured to cause said printer to print documents having both (i) machine-readable pattern <u>printed in the first ink, wherein the pattern is configured</u> ~~adapted~~ to enable a digital pen to acquire data to enable its position in said pattern to be determined, and (ii) human-discernable content<u>, printed in the second ink,</u> that is not read by said pen in use, said system being <u>configured</u> ~~adapted~~ to route data representative of content colour to (i) a colour separation process, and to (ii) a half-toning process, and to (iii) a masking process, and where said system is <u>configured</u> ~~adapted~~ to route data representation of pattern so as to by-pass a half-toning process.

84. (Currently Amended) A control system according to claim 83 <u>configured</u> ~~adapted~~ to route data representative of pattern so as to by-pass a masking process.

85. (Currently Amended) A control system according to claim 83 <u>configured</u> ~~adapted~~ to route data representative of content through a linearisation process, and <u>configured</u> ~~adapted~~ to route data representation of pattern so as to by-pass said linearisation process.

86. (Currently Amended) A control system according to claim 83 <u>configured</u> ~~adapted~~ to route data representative of pattern so as to by-pass a masking process and <u>configured</u> ~~adapted~~ to route data representative of content through a linearisation process, and

configured ~~adapted~~ to route data representation of pattern so as to by-pass said linearisation process.

87.   (Currently Amended) A method of printing <u>a document</u> ~~documents having printed thereupon both~~:

~~(i) machine-readable position-determining pattern adapted to enable a machine reader to determine its the pen's position in a pattern space, and~~

~~(ii) human-discernable content adapted not to be read by said machine reader;~~

~~the method~~ comprising<u>:</u>

digitally printing [[the]] <u>a human-discernable</u> content and <u>a machine-readable</u> position-determining pattern<u>, configured to enable a digital pen to determine the pen's position in a pattern space</u> onto the document using [[the]] <u>a single</u> ~~same~~ digital printer, <u>wherein</u> the <u>digital</u> printer <u>includes</u> ~~having~~ a first ink which is not machine-readable at a particular wavelength of electromagnetic radiation and a second ink that is machine-readable at the said particular wavelength <u>;</u> [[,]] and

printing the content with the first ink and not the second ink, at least where said content overlies said pattern <u>;</u> [[,]] and

printing the pattern using the second ink;

wherein data representative of content is half-toned, and wherein data representation of pattern bypasses a half-toning process.

88. (Previously Presented) A method according to claim 87 wherein data representative of content is operated upon by a masking process, and data representation of pattern bypasses a masking process.

89. (Currently Amended) A method of printing on demand a page or other article ~~with both a machine-readable position-determining pattern readable at a specific, optionally non-visible, wavelength and also human-discernable content using a single digital printer responsive to a print command from a user's processor~~, the method comprising:

printing, using a single digital printer, a machine-readable position-determining pattern with a first ink, wherein the pattern is configured to enable a digital pen to determine the pen's position in a pattern space, and wherein the pattern is readable at a specific, optionally non-visible, wavelength;

printing, using the single digital printer, human-discernable content in a second ink; and

~~having content data and pattern data and~~ processing the content data differently from the pattern data during data processing performed to print the document.

90. (Currently Amended) A method of printing according to claim 89 further comprising ~~comprising using a single digital printer responsive to a print command from a user's processor, and the method comprising~~ treating the pattern as text content in a printer driver, and printing the pattern using exclusively one ink that is readable by a machine at said non-visible wavelength, or exclusively using a plurality of inks that are readable at said non-visible wavelength, and printing the content, at least that content which is superposed with said pattern, using exclusively an ink ~~, or inks,~~ that [[are]] is not machine-readable at said non-visible wavelength.

91. (Currently Amended) A method of printing according to claim 89, the method comprising taking [[a]] an RGB version of an image from a computer and isolating the pattern in its own colour plane, optionally during a colour separation process, content being printed with other available colour planes not including said pattern colour plane.

92. (Previously Presented) A method according to claim 91 in which content colour plane data undergoes a half-toning and masking operation in order to determine what content, if any, is printed at each pixel of the printing operation, and wherein pattern colour plane data bypasses the half-toning operation.